




BW9328

Fasson® Fasclear 300 /S692N/BG40#WH imp

Fasson®
Fasclear 300
A transparent satin
finished co-extruded
polyolefin film

Applications



Key Features

- Adhesive is specifically designed to exhibit excellent wet-out characteristics on clear films
- The specially engineered film combines good MD rigidity, and hence dispensability, with high CD squeezability
- The transparent finished film gives good blend into todays matte plastic containers, without the need for color matching

Spec Code: BW9328 Issue date: Sep, 2020

Facestock

A transparent satin finished co-extruded polyolefin film, optimally designed for roll label use.

Basis Weight: 71 g/m2 \pm 10% ISO536 Caliper: 0.076 mm \pm 10% ISO534

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

A super calendared white glassine paper with excellent roll label converting properties.

Basis Weight: 60 g/m2 \pm 10% ISO536 Caliper: 0.051mm \pm 10% ISO534

Performance data

loop Tack (st,st)-FTM 9: 10.0 20 min 90° Peel (st,st)-FTM 2: 5.5 24 hour 90° Peel (st,st)-FTM 2: 7.0 Minimum Application Temperature: -5°C

After labeling 24H, Service Temperature Range: -29°C~+93°C

Adhesive Performance

It is a clear permanent adhesive designed for prime labeling applications including squeezable and clear labeling applications. It features good die cutting and strip performance. It is suitable for applications where compliance with FDA 175.105 is required. This section covers applications where for indirect or incidental contact food, cosmetic or drug products.

Applications and use

Applications are predominantly in cosmetics and toiletries: areas requiring high quality graphics together with consistent functional performance during automatic application and in end use. The specially engineered film combines good MD rigidity, and hence dispensability, with high CD squeezability, for use on containers where continued flexing during end use is expected. The clear finished film gives good blend into todays clear plastic containers, without the need for color matching. Material is a good alternative in those application areas where PVC is no longer accepted.

The above does not represent any guarantee or warranty and the Purchaser must independently determine the suitability of the products for the Purchaser's purposes.


Conversion/printing

Printable by web screen, letterpress, flexo, gravure, hot foil. Printing in the flexo and letterpress, UV inks are recommended. To ensure optimum wettability and ink bond, additional in-line corona treatment is required. Ink testing is necessary before production. Sharp film tooling preferably in flatbed, are important to ensure smooth conversion. Need avoid too much rewinding tension to causing bleeding on standard web-fed presses using typical film tooling. Flat bed performance is good while solid and magnetic rotary dies need additional care.

Shelf life

One year when stored at 23 \pm 2°C at 50 \pm 5% RH.

Fasson® Fasclear300 /S692N/BG40#WH imp



Fasclear300
S692N
BG40#WH imp

Asia Pacific

32/F., Skyline Tower 39 Wang Kwong Road Kowloon Bay, Kowloon, Hong Kong

Warrenty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but but do no constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsable for claims beyond the replacement value of the defective product or in any way

liable or responsable for consequential or incidental damages. NO EXPRESS WARRANTIES, WHETHER OF MERCHANTIBILITY OR FITNESS FOR ANY ARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERNATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.